Pure and Simple

The CM Centre's symmetrically arranged driver line-up of twin 130mm Kevlar® cone bass/midrange units and a 25mm Nautilus™ tube-loaded aluminium tweeter are integrated by a minimalist, ear-tuned, first order network made possible by the remarkably wide bandwidth of the drivers.

Technical Specifications

Technical features	Nautilus™ tube loaded aluminium dome tweeter Kevlar® brand fibre cone bass / midrange Flowport™ Magnetic shielding
Description	2-way vented-box system
Drive units	1x ⌀25mm (1 in) aluminium dome high-frequency 2x ⌀130mm (5 in) woven Kevlar® cone bass / midrange
Frequency range	-6dB at 45Hz and 50kHz
Frequency response	55Hz - 22kHz ±3dB on reference axis
Dispersion	Within 2dB of reference response Horizontal: over 20° arc Vertical: over 60° arc
Sensitivity	85dB spl (2.83V, 1m)
Harmonic distortion	2nd and 3rd harmonics (90dB, 1m) <1% 100Hz - 22kHz <0.5% 200Hz - 22kHz
Nominal impedance	8Ω (minimum 4.3Ω)
Crossover frequency	4kHz
Recommended amplifier power	30W - 120W into 8Ω on unclipped programme
Max. recommended cable impedance	0.1Ω
Dimensions	Height: 166.5mm (6.6 in) Width: 480mm (18.9 in) Depth: 255mm (10 in) cabinet only 275mm (10.8 in) including grille and terminals
Net weight	11.5kg (25.3 lb)
Finish	Cabinet: Real wood veneers: Wengé, Rosenut Painted finish: Gloss Black Grille: Black

Gloss black   Wengé   Rosenut