

803S

B&W

Bowers & Wilkins



The 803S is the largest model to feature our aluminium dome tweeter, which has been enhanced with a new design of surround that operates better in unison with the dome. It has allowed the driver's low-end response to be extended in order to use the simple single component crossover design. Tube loaded for extra clarity, and mounted separately on top of the main cabinet for optimum dispersion of sound, the tweeter blends seamlessly with the FST™ midrange driver to create a solid, three-dimensional sound stage.

Bass is supplied by two 7" diameter Rohacell® cone drivers, supplemented by a front-firing Flowport™, its now familiar dimples ensuring smoother airflow through the port to give greater dynamics, unsullied by distracting turbulence noise.

Description: 3-way vented-box system
Frequency Range: -6dB at 28Hz and 50kHz
Frequency Response: 35Hz – 22kHz ±3dB on reference axis
Sensitivity: 90dB spl (2.83V, 1m)

Nominal Impedance: 8Ω (minimum 3.0Ω)
Dimensions: H 1063mm W 291mm D 433mm
H 41.9" W 11.5" D 17"
(not including feet)
Weight: 41 kg / 90 lbs.
Finishes: Cherrywood, Rosenut, Black Ash

B&W Bowers & Wilkins

B&W Group Ltd
Dale Road
Worthing West Sussex
BN11 2BH England
T +44 (0) 1903 221800
F +44 (0) 1903 221801
info@bwgroup.com
www.bwspeakers.com

UK Group (UK Sales)
T +44 1903 221 500
E uksales@bwgroup.com

B&W Group North America
T +1 978 664 2870
E marketing@bwgroupusa.com

B&W Group Asia Ltd
T +852 2 869 9916
E showroom@bwgroup.hk