



See nothing, hear everything

Need big sound, slamming bass and audiophile bass extension, but don't want to see where it comes from? Then the new ISW-4 in-wall subwoofer is the product for you. Its two long-throw 200mm drivers allows the ISW-4 to move large volumes of air needed for high-quality low-frequency output, but is nicely hidden away inside a wall.

Technical Specifications

Description	In-wall Subwoofer
Technical Specifications	
Driver size	2 x 8" (200mm)
Cone material	Paper / Aramid Fibre cone
Nominal Impedance	8Ω (minimum 6.3Ω)
Power rating	250W
Frequency response (-3dB)	25Hz – 222Hz
Frequency range (-6dB)	19Hz – 400Hz
Baffle	
Baffle dimensions	Height: 494mm (19.5in) Width: 264mm (10.4in) Depth: 21mm (0.8in)
Cut-out size	Height: 485mm (19.1in) Width: 255mm (10.0in)
Net weight	6.4kg (14.1lb)
Frame/grille finish	Semi-matt white (paintable)
Back Box	
Description:	Closed-box subwoofer
Dimensions	Height: 1,406mm (55.4in) Width: 345mm (13.6in) Depth: 86mm (3.4in)
Material	MDF
Bracing	Yes
Volume	27.5L
Net weight	9.6kg (21.2lb)
Amplifier (mandatory)	CDA-4D compact distribution amplifier